

# A REVIEW ON COGNITIVE RADIO BASED SPECTRUM SENSING TECHNIQUES

Dharmendra Kumar Fageria<sup>1</sup>, Rahul Kumar Garg<sup>2</sup>

Assistant professor, Electronics and Communication Engineering  
Shekhawati Institute of Engineering and Technology, Sikar, Rajasthan, India.

**Abstract:** Due to underutilization of radio spectrum allocated to primary users and ever increasing demand of spectrum, Cognitive Radio has emerged as a well-known dynamic spectrum utilization technique. Spectrum sensing is an essential part of Cognitive radio which enable the user to sense the white and grey spaces in RF environment. This paper enlightens the method of spectrum sensing, the recent advancements and the problems associated with the efficient use of it.

**Keywords:** Cognitive Radio, Spectrum Sensing techniques.

## I. INTRODUCTION

Cognitive Radio(CR) is a dynamic adaptive, intelligent radio network technology that can automatically detect white spaces in the available radio spectrum and change transmission parameters enabling more communications to run concurrently and also improve radio operating behavior. The term 'white spaces' here means the unoccupied channels or bandwidths not in use at that particular time interval which has been allocated to the licensed user known as primary user. To enable the use of these white spaces the CR Network make use of the technique known as Spectrum Sensing. It may be defined as the technique through which Cognitive Radio get enabled to search for vacant channels in the electromagnetic spectrum space.

From this definition we can deduce three primary cognitive radio tasks:

- 1) Spectrum Sensing (senses its operational electromagnetic environment)
- 2) Channel Identification (to maximize throughput)
- 3) Transmit power control & Dynamic spectrum management (dynamically and autonomously adjust its radio operating parameters to modify system operation, mitigate interference, facilitate interoperability)

This definition also suggests that Cognitive Radio are self-configurable radios that sense the spectral environment, autonomously & dynamically detect and interpret the changes occurring and facilitate coherent, reliable wireless communication without causing interference with existing licensed users. Exploitation of spectrum needs efficient spectrum management that comprises of both static and dynamic processes. Static allocation technique is fixed by regulatory mechanisms (i.e. static in temporal and spatial dimensions) while newer approach works with dynamic spectrum management for dynamic allocation in wireless communication system. Basic methodology of cognitive radio based on dynamic spectrum management, for accessing the spectrum opportunistically is divided into four phases:- Spectrum Sensing involves "spectrum hole" detection for

efficient usage of dynamic allocation technique. Spectrum Hole is the potential opportunity to use the spectrum by a secondary user without interfering with licensed user. However, definition of "Spectrum Hole" in time and frequency domain may be more nuanced [3]. Spectrum allocation follows spectrum sensing and refers to interpreting the frequency band to use. In case of multiple users, sharing of spectrum can occurs. In spectrum allocation, bandwidth sensing is necessary to distinguish between the margins of bandwidth for proper detection of signals.

Spectrum Configuration is adaption and estimation of the parameter required for transmission. Cognitive Radio may potentially reconfigure itself according to required modulation scheme, carrier frequency, transmit power etc. and this reconfiguration must occur very quickly.

Spectrum transmission is the phase where system identifies the transmission of other units with primary user. It must be able to detect any interference accurately to minimize the number of false detections. After reliable identification of the available spectrum holes, the cognitive radio system needs to estimate the transmission parameters such as spectrum bandwidth, power levels, Power control, bit rate control, etc.

Prime advantages offered by Cognitive Radio are

- 1) Improved efficiency by allowing unlicensed users to exploit spectrum whenever it will not cause interference to licensed users.
- 2) Highly Reliable communication as and when required. Accurate Spectrum sensing is one of the major challenges in Cognitive Radios. We review Cognitive Radio basic model in Section 1 & 2.

The rest of the paper is organized as follows: We review various spectrum sensing methodologies and their strengths and shortcomings in Section 3. Section 4 discusses challenges/issues in cognitive radio systems. Section 5 provide small introduction of dynamic spectrum management (DSM). Finally, Section 6 concludes the paper and outlines potential future research areas.

## II. COGNITIVE RADIO – BASIC MODEL

Both licensed and unlicensed frequency bands are available for opportunistic exploitation by Cognitive Radios. However, in the licensed band, detection of existing legacy users - also known as primary users - is of prime importance to avoid interference with cognitive radio transmission, by continuously hopping to next vacant frequency band [4]. From cognitive radio perspective, primary users are generally defined as the users who have license to use a given frequency spectrum in a given time window. Similarly, Secondary Users (SUs), are unlicensed users having no

legacy rights to the spectrum and thus having low priority as compared to PUs. To establish reliable communication, SUs need to opportunistically exploit this spectrum without causing interference to primary users [5,6,7].

### III. SPECTRUM SENSING TECHNIQUES

#### 3.1. Spectrum Sensing – An Overview

Accurate spectrum sensing has remained the fundamental problem in Cognitive Radio. It is so important because reliability of transmission without any interference to PUs depends squarely on accurately detecting the presence of any PUs. Presence or absence of PUs will facilitate identification of spectrum holes which can be exploited by SUs.

In cognitive radio, process of sensing of spectrum has three main objectives:

- Continuous radio channel monitoring to sense the temporal spectrum occupancy by a PU at a given time without interference.
- Continuous sensing for spectrum holes to dynamically allocate spectrum as and when needed.
- Estimation of transmission parameters like power levels, interference temperature, and conditions required for dynamic spectrum management.

A number of solutions have been proposed over the years to facilitate accurate spectrum sensing [12].

From implementation point of view, Spectrum sensing can be classified on the basis of hardware architecture which makes use of various spectrum sensing methodologies [13, 14, 15]. There are two architectures under consideration: Single Radio architecture where a single cognitive radio is used for both spectrum sensing and transmission. It is simple and low cost but less accurate. Dual Radio architecture utilizes two radios making it complex and costly as compared to Single Radio Architecture but is more accurate [5].

### IV. CHALLENGES AND ISSUES IN COGNITIVE RADIO

Despite progress in research on Cognitive radio techniques, issues remain in implementation of available theoretical methods due to several limitations [31]. Some of these limitations are discussed below.

#### 1. Hidden terminal problem

This problem is characterized by missing detection of primary user due to location of transmitter w.r.t the primary receiver. This causes interference with primary user transmission. Cooperative sensing addresses this problem to some extent by information sharing but other techniques still require better solutions [32].

#### 2. Hardware requirements

Most of the detectors are based on Energy Detection techniques because of simplicity of implementation. However, these energy detectors suffer from some drawbacks. Also, presence of several identically distributed spectrally superimposed signals will confuse most energy detection schemes, preventing the interceptor from determining anything more than the knowledge that signals are present in the environment. Another significant drawback is that energy detection cannot distinguish among different types of transmissions or interference from signals. More

computationally extensive techniques still lack in hardware implementation because of various logistical, design and financial limitations [5].

#### 3. Scanning a very wide spectrum range

A cognitive radio needs to continuously scan a verywide range of frequency bands in order to sense and identify spectrum holes. To sense a very large frequency band, a sufficiently large sampling rate will be needed. Simple hardware implementation of such a wideband cognitive system is still a challenge.

#### 4. Security

In cognitive radio, security concerns remain a concern and security standards need to be developed. Some common scenarios have been explored. For e.g. a malicious user can impersonate a primary user and compromise the cognitive network. It has been named as primary user emulation (PUE) attack [33]. A primary user authentication scheme is proposed in [34]. Primary user identification using a public key encryption system is discussed in [35] as a mitigation exercise to repair a compromised network.

### V. DYNAMIC SPECTRUM MANAGEMENT

Dynamic spectrum management (DSM) efficiently solves problem of spectrum scarcity and spectrum under-utilization in wireless communication. This technology covers frequency assignment with dynamic channel/spectrum allocation (DSA) and contains information about spectrum sensing for both primary and secondary users. Cognitive radio has been one of the most vital applications of dynamic spectrum management. DSM manually allocates un-used spectrum, after link adaption as it combines unused channel on basis of pre cancellation of estimated interference for multiple user (i.e. both primary and secondary users). DSM is a promising tool for many radio technologies in wireless communication, as it provides broad bandwidth for spectrum sensing.

### VI. CONCLUSION & FUTURE WORK

In this paper, Cognitive Radio and various spectrum sensing techniques have been reviewed. Performance and accuracy of individual spectrum sensing techniques have been investigated with attention to newer approaches to detection problem. Challenges have been discussed. More research is needed to simplify cognitive radio implementation models, associated security aspects and accuracy of spectrum sensing techniques. In particular, the efficacy of spectrum sensing algorithms in noisy and fading environments needs attention.

### REFERENCES

- [1] Allen B. Mac Kenzie et al., "Cognitive Radio and Networking Research at Virginia Tech", Proceedings of the IEEE, Vol. 97, No. 4, April 2009.
- [2] Amir Ghasemi, Elvino S. Sousa, "Spectrum Sensing in Cognitive Radio Networks: Requirements, Challenges and Design Trade-offs", IEEE Communications Magazine April 2008.
- [3] Anita Garhwal and ParthaPratim Bhattacharya, "A Survey on Spectrum Sensing Techniques in

- Cognitive Radio”, International Journal of Computer Science & Communication Networks, Vol. 1(2), 196-206.
- [4] Anirudh M. Rao, B. R. Karthikeyan, Dipayan Mazumdar, Govind R. Kadambi, “Energy Detection Technique For Spectrum Sensing In Cognitive Radio”, SASTECH, Volume 9, Issue 1, April 2010.
- [5] Ashish Bagwari and Geetam Singh Tomar. “Improved Spectrum Sensing Technique using Multiple Energy Detectors for Cognitive Radio Networks” International Journal of Computer Applications 62(4):11-21, January 2013.
- [6] A. Nasipuri and S. R. Das, “Multichannel CSMA with signal power-based channel selection for multihop wireless networks”, Proc. of IEEE Fall Vehicular Technology Conference (VTC 2000), Sept. 2000.
- [7] Danda B. Rawat and Gongjun Yan “Spectrum Sensing Methods and Dynamic Spectrum Sharing in Cognitive Radio Networks: A Survey”, International Journal of Research and Reviews in Wireless Sensor Networks, Vol. 1, No. 1, March 2011.
- [8] Dong-Chan Oh et al. 2009 and Yong-Hwan Lee, “Energy Detection Based Spectrum Sensing for Sensing Error Minimization in Cognitive Radio Networks”, International Journal of Communication Networks and Information Security (IJCNIS), Vol. 1, No. 1, April 2009.
- [9] Guicai YU, Chengzhi LONG, Mantian XIANG, Wei XI, “A Novel Energy Detection Scheme Based on Dynamic Threshold in Cognitive Radio Systems”, Journal of Computational Information Systems 8: 6 (2012) 2245–2252.
- [10] Ghalib A. Shah Ozgur B. Akan, “CSMA-based Bandwidth Estimation for Cognitive Radio Sensor Networks”, proc. of IEEE, NTMS 2012, May 2012.
- [11] Hano Wang, Gosan Noh, Dongkyu Kim, Sungtae Kim, and Daesik Hong, “Advanced Sensing Techniques of Energy Detection in Cognitive Radios”, Journal of Communications and Networks, Vol. 12, No. 1, February 2010.
- [12] Ian F. Akyildiz, Won-Yeol Lee, Mehmet C. Vuran, and Shantidev Mohanty, “A Survey on Spectrum Management in Cognitive Radio Networks”, IEEE Communications Magazine, April 2008.
- [13] I. F. Akyildiz, W.-Y. Lee, M.C. Vuran, S. Mohanty, “Next generation/dynamic spectrum access/cognitive radio wireless networks: a survey”, Computer Networks, vol. 50, no. 13, Sep. 2006, pp. 2127-2159
- [14] J. Hwang and H. Yoon, “Dynamic spectrum management policy for cognitive radio: An analysis of implementation feasibility issues” New Frontiers in Dynamic Spectrum Access Networks, 2008. DySPAN 2008, 3rd IEEE Symposium on, pp. 1–9, Oct. 14-17 2008.
- [15] Joseph Mitola III and Gerald Q. Maguire, Jr. “Cognitive Radio: Making Software Radios More Personal” IEEE Personal Communications, August 1999.
- [16] Juan Andrés Bazerque, Georgios B. Giannakis, “Distributed Spectrum Sensing For Cognitive Radio Networks By Exploiting Sparsity”, IEEE Transactions On Signal Processing, Vol. 58, No. 3, March 2010.
- [17] Lu Wei, Tirkkonen, “Spectrum Sensing in the Presence of Multiple Primary Users”, Communications, IEEE Transactions on Volume: 60, Issue: 5, May 2012.
- [18] Mansi Subhedar and Gajanan Birajdar, “Spectrum Sensing Techniques in Cognitive Radio Networks: A Survey” International Journal of Next-Generation Networks (IJNGN) Vol.3, No.2, June 2011.
- [19] Nigel Laflin and Bela Dajka, BBC, “A Simple Guide to Radio Spectrum”, EBU Technical Review, January-2007.
- [20] Pandharipande and J. Linnartz, “Performance Analysis of Primary User Detection in a Multiple Antenna Cognitive Radio,” Communications, 2007. ICC’07. IEEE International Conference on, pp. 6482–6486, 2007.
- [21] Ralston and E. D. Reilly, Encyclopedia of Computer Science. New York: Van Nostrand, 1993, pp. 186–186.
- [22] Report of the Spectrum Efficiency Working Group, FCC Spectrum Policy Task Force, Nov. 2002. [Online Available: <http://www.fcc.gov/sptf/reports.html>].
- [23] S. Haykin, “Cognitive Radio: Brain-empowered wireless communications”, IEEE Journal on Selected Areas in Communications, Special Issue on Cognitive Networks, vol. 23, pp. 201-220, February 2009.
- [24] Simon Haykin, David J. Thomson, Jeffrey H. Reed, “Spectrum Sensing for Cognitive Radio” Proceedings of the IEEE, Vol. 0018-9219, 2009 IEEE 97, No. 5, May 2009.
- [25] Takeshi Ikuma and Mort Naraghi-Pour, “A Comparison of Three Classes of Spectrum Sensing Techniques”, IEEE GLOBECOM proceedings, November, 2008.
- [26] Tevfik Yucek and Hu Seyin Arslan “A Survey of Spectrum Sensing Algorithms for Cognitive Radio Applications”, IEEE Communications Surveys & Tutorials, Vol. 11, No. 1, First Quarter 2009.
- [27] Tugba Erpek, Mark Lofquist, Ken Patton, “Spectrum Occupancy Measurements Loring Commerce Centre Limestone, Maine” Shared Spectrum Company 1595 Spring Hill Road, Suite 110 Vienna, VA 22182-2228, September 18-20, 2007.
- [28] Won-Yeol Lee and Ian. F. Akyildiz, “Optimal Spectrum Sensing Framework for Cognitive Radio Networks”, IEEE Transactions on Wireless Communications, Vol. 7, no. 10, October 2008.
- [29] Yue Wang, Zhi Tian, Chunyan Feng, “Collecting Detection Diversity and Complexity Gains in Cooperative Spectrum Sensing”, IEEE Transactions

- On Wireless Communications, Vol. 11, No. 8, August 2012.
- [30] Y. Chen, "Improved Energy Detector for Random Signals in Gaussian Noise", *IEEE Transactions, Wireless Communication*, Volume: 9, Issue: 2 558-563 (2010).
- [31] Y. Zeng, Y. Liang, and R. Zhang, "Blindly Combined Energy Detection for Spectrum Sensing in Cognitive Radio" *Signal Processing Letters, IEEE*, vol. 15, 2008.
- [32] Zhi Tian, Georgios B. Giannakis, "A Wavelet Approach to Wideband Spectrum Sensing for Cognitive Radios", *Cognitive Radio Oriented Wireless Networks and Communications, IEEE*, Volume 1, June 2006.
- [33] Z. Tian and G. Giannakis, "Compressive sensing for wideband cognitive radios," *Proc. IEEE International Conference on Acoustics, Speech, and Signal Processing*, Honolulu, HI, USA, April 2007, pp. 1357–1360.