

## VEGETABLE OIL AS FUEL IN C.I. ENGINE: PROBLEMS AND POSSIBLE SOLUTIONS

Gautam Sahu<sup>1</sup>, Sahil Singh<sup>2</sup>, Ms. Promila<sup>3</sup>  
<sup>1,2</sup>Students, <sup>3</sup>Assistant Professor

Department of Mechanical Engineering  
Mahavir Swami Institute of Technology, Sonapat, Haryana, India

**Abstract:** - Vegetable oil has slightly lower calorific value than diesel oil. This can be attributed to presence of oxygen in the molecules of vegetable oils. Vegetable oil has cetane number about 35 to 40 depending upon the composition whereas diesel fuel has a cetane number around 45. certain functional groups and poor volatility is responsible of their comparatively low cetane number. Vegetable oil and diesel differs greatly in other properties. Their kinematic viscosity is several times greater than for diesel oil the high viscosity of vegetable oils lead to pumping and atomization problems in the normal diesel fuel injection system, which creates filter plugging and cold starting high carbon residue causes heavy smoke emission and carbon deposition on the injection nozzle tips and in the combustion chamber. There are also problems of incompatibility with engine lubricants. The poor volatility makes vegetable oil difficult to vaporize and ignite, this leads to thermal cracking resulting in heavy smoke emission and carbon deposition in the combustion chamber. This tendency is partly due to higher fuel viscosity. Vegetable oil dilutes the lubricating oil and forms sludge on all parts of the engine. Which come in contact with lubricating oil. Filter plugging can be minimized if crude degummed oils are passed through a four-micrometer in the paper author has suggested various ways to overcome the difficulties associated with vegetable oil to be used in CI engine.

**Keywords:** - Vegetable oil, cold starting, degumming, plugging.

### 1. Introduction

Vegetable Oil as Fuel for Compression Ignition Engines After the first commercial shock in 1973 and secondly in 1979 due to sudden increase in prices of petroleum products by the supplying countries attention was diverted to find out the substitute to diesel fuel [8]. The various alternative fuel options considered for diesel substitute are hydrogen, biogas, producer gas, methanol ethanol, natural gas, coal water slurry and vegetable oils. Hydrogen appears better alternate but problem related to its production, hazardous nature, storage and handling are yet to be sorted out. Biogas and producer gas are of low calorific value and can be substitute to diesel only up to 80% in stationary application. More over there is problem of storage because of gaseous state in nature. Beside producer gas being a poisonous gas may cause serious health hazards for the operator. Methanol and ethanol has poor energy content, have a low cetane number a poor lubrication properties, hence it may lead to problems in fuel injection

system. Further alcohols cannot be used in compression ignition engine by conventional methods. It requires a very high compression ration of the order of 28 for its use in conventional compression ignition engines. Alcohols show a better response to spark ignition engines the cylinders. Storage of the gas in cylinders and possibility of leakage while in use are the hurdles to overcome. Coal water slurry is the coal fuel that makes the economic sense. A coal fueled diesel engine holds the promise of rugged, modular heat engines that uses cheap, abundant fuel, the concept of coal water slurry as compression ignition engine fuel is still in initial stage due to problems associated with wear of position rings, cylinder liners and erosion of fuel nozzle. Further the use is restricted in slow and medium speed engines.

### 2. DIFFICULTIES AND REMEDIES WITH VEGETABLE OIL AS FUEL

#### Advantages

From the review of literature available in the field of vegetable oil usage, many advantages are noticeable the following are some of the advantages of using vegetable oil as I.C. engine in India:

- I. Vegetable oil is produced domestically which helps to reduce costly petroleum imports.
- II. Development of the bio-diesel industry would strengthen the domestic, and particularly the rural agricultural economy of agricultural based countries like India.
- III. It is biodegradable and non-toxic:
- IV. It is a renewable fuel that can be made from agricultural crops and or other feed stocks that are considered as waste:
- V. It has 80% heating value compared to that of diesel:It contains low aromatics
- VI. It has a reasonable cetane number and hence possesses less knocking tendency:
- VII. Low sulphur content and hence environment friendly:
- VIII. Enhanced lubricity, thereby no major modification is required in the engine: X. Personal safety is improved(flash point is 1000C higher than that of diesel):
- XI. It is usable within the existing petroleum diesel infrastructure (with minor or no modification in the engine):

#### Challenges and Difficulties

The major challenges they face the use of vegetable oil as

L.C. engine fuels are listed below

- I. The price of vegetable oil is dependent on the feed stock price:
- II. Feed stock homogeneity, consistency and reliability are questionable:
- III. Homogeneity of the product depends on the supplier, feed stocks and production methods:
- IV. Storage and handling is difficult (particularly stability in long term storage):
- V. Flash point in blends is unreliable:
- VI. Compatibility with I.C. engine material needs to be studied further:
- VII. Cold weather operation of the engine is not easy with vegetable oils:
- VIII. Acceptance by engine manufacturers is another major difficulty:
- IX. Continuous availability of the vegetable oils needs to be assured before embarking on the major use of it in I.C. engines.

#### Technical Difficulties

The major technical areas (with respect to the use of vegetable oils as fuels in I.C. engines), which need further attention are the following:

- I. Development of less expensive quality tests:
- II. Study of the effects of oxidized fuel on engine performance and its durability:
- III. Emission testing with a wide range of feed stocks:
- IV. Studies on developing specific markets such as mining, municipal water supplies etc. Which can specify bio-diesel as the fuel choice for environmentally sensitive areas:
- V. Co-product development like the recovery of glycerol at reduced cost:
- VI. Efforts to be focused on responding to fuel system performance, material compatibility, petroleum additive compatibility and low fuel stability under long term storage:
- VII. Continued engine performance, emissions and durability testing I a variety of engine types and sizes need to be developed to increased consumer and manufacture confidence:
- VIII. Environmental benefits offered by vegetable oil over diesel fuel needs to be popularizes:
- IX. Studies are needs to reduce the production cost, develop low cost feed stocks and identify potential markets in order to balance cost and availability:
- X. Research on the effect of glycerol on engine durability, emission and material compatibility:
- XI. Development of additives for improving cold flow properties, material compatibility and prevention of oxidation in storage, etc.

Vegetable oil has slightly lower calorific value than diesel oil. This can be attributed to presence of oxygen in the molecule of vegetable oils. Vegetable oil has cetane number about 35 to 40 depending on composition whereas diesel fuels have a cetane number around 45. Certain functional

groups and the poor volatility is responsible for their comparatively low cetane number.

Vegetable oil and diesel differs greatly in other properties. Their kinematic viscosity is several times greater than for diesel oil. The kinematic viscosity of vegetable oil at 40 C is in the range of 35 to 45 cSt whereas for diesel oil is 2-4 cSt. Other disadvantages of vegetable oil are large carbon residue

1. The high viscosity of vegetable oils lead to pumping and atomization problems in the normal diesel fuel injection system, which creates filter plugging and cold starting.
2. High carbon residue causes heavy smoke emission and carbon deposition on the injection nozzle tips and in the combustion chamber.
3. There are also problems of incompatibility with engine lubricants.
4. The poor volatility makes vegetable oil difficult to vaporize and ignite. This leads to thermal cracking resulting in the heavy smoke emission and carbon deposits in the combustion chamber. This tendency is partly due to higher fuel viscosity
5. Vegetable oil dilutes the lubricant oil and forms sludges on all parts of engine, which come in contact with lubricating oil.

#### Remedies

1. Filter plugging is minimized if crude degummed oils are passed through a four micrometer filter.
2. Starting problems should be overcome by starting aids such as glow plugs and fuel heaters.
3. Modification of fuel

#### Modification of Fuel

The alternative diesel fuels must be technically and environmentally acceptable, and economically competitive. From the viewpoint of these requirements, triglycerides (vegetable oils/animal fats) and their derivatives may be considered as viable alternatives for diesel fuels. The problems with substituting triglycerides for diesel fuels are mostly associated with their high viscosity, low volatility and polyunsaturated character. The problems have been mitigated by developing vegetable oil derivatives that approximate the properties and performance and make them compatible with the hydrocarbon-based diesel fuels through the pyrolysis, micro emulsification, dilution and Transesterification.

#### Dilution

Dilution of vegetable oils can be accomplished with such materials as diesel fuels, solvent or ethanol.

### 3. CONCLUSION

Researchers in various countries carried out many experimental works using vegetable oils as I.C. engine fuel substitutes. These results showed that thermal efficiency was comparable to that of diesel with small amounts of power loss while using vegetable oils. The particulate emissions of vegetable oils are higher than that of diesel fuel with a reduction in NOx. Vegetable oil methyl esters gave

performance and emission characteristics comparable to that of diesel. Hence they may be considered as diesel fuel substitutes. Raw vegetable oil can be used as fuel in diesel engines with some minor modifications. The use of vegetable oils as I.C. engine fuels can play a vital role in helping the developed world to reduce the environmental impact of fossil fuels.

### REFERENCES

1. www.biodiesel.com
2. Narayan CM. Vegetable oil as engine fuels-prospect and retrospect. Proceedings on Recent Trends in Automotive Fuels. Nagpur, India,2002
3. Fangrui Ma. Milford A. Bio-diesel production-review. Bioresource Technology, New Delhi, India, 1999.
4. Czerwinski J. Performance of D.I. Diesel engine with addition of ethanol and rapeseed oil. SAE 940545, 1994.
5. Srinivasa Rao P, Gopalakrishna KV. Esterified oils as fuel in diesel engines, 11th National Conference on I.C. Engines, I.I.T. Madras, India,1983.
6. Ramadhas AS, Jayaraj S, lakshmi Narayana Rao K. Experimental investigation on non-edible vegetable oil operation in diesel engine for improved performance, National Conference on Advance in Mechanical Engineering, J.N.T.U., Anantapur, India, 2002. [7] V. Domkundwar, A course on I.C. engines., Dhanpat Rai & Co (2001)
7. Recep altan, Selim Cetinkay, Huseyin Serdar Yucesu. The potential of using vegetable oil fuels as fuel for diesel engines, No 529538, Energy Conversion and Management, 2001.
8. Christopher W. The practical implementation of bio-diesel as an alternative fuel in service motor coaches SAE 973201, 1997 [10] Montague X. Introduction of rapeseed methyl ester in Diesel fuel-the French National Program, SAE 962065, 1996.
9. Hohl GH. Rape oil methyl ester and used cooking oil methyl ester as alternative fuels, SAE 952755, 1995.
10. Norbert Hemmerlein, Volker Korte, and Herwig Richter. Performance, Exhaust emission and durability of modern diesel engines running on rapeseed oil, SAE 910848, 1991.
11. Jose M.D ESANTES, Jean Arragle, Santiago Ruiz. Characterization of the injection-combustion process in DI Diesel engine running with Rape seed oil methayl ester, SAE 199-01-1497, 1999.
12. Tadashi, Young. Low carbon build up, low smoke and efficient diesel operation with vegetable oil by conversion to monoesters and blending with diesel oil or alcohols, SAE 841161, 1984.
13. Senatore A. A comparative analysis of combustion process in D.I. Diesel engine fueled with bio-diesel and diesel fuel, SAE 2000-010691, 2000.
14. Choi CY. Effect of bio-diesel blended fuels and multiple injections on D.I diesel engine, SAE 970218, 1997.
15. Peter Klee.Characterization of different vegetable oil fuel with regard to their suitability as diesel fuel substitutes under special consideration of their physical and chemical properties, SAE VDI Nr.375, 1983.
16. Zhang Y. Combustion analysis of ester of soyabean oil in a diesel engine, SAE 960765, 1996.
17. Barsic NJ, Humke H. Performance and emission characteristics of a naturally aspirated diesel engine with vegetable oil, SAE 810262, 1981.
18. Masjuki HH, Kakm MA, Maleque MA, Kubo A, Nonaka T. Performance, emissions and wear characteristics of an I.D.I diesel engine using coconut blended oil, part D 215,I.Mech. E., 2001.
19. C.A.Silvico, R.Carlos,V.G.Marious, S.R.Leonardodos and F.Guilherme.Performance of a diesel generator fueled with palm oil. Journal of Fuels 81 (2002).pp.2097-2102. [33] www.goodnewsindia.com
20. The Hindu, Daily Newspaper dated 4.1.2003.